

# Smappee Connect



- Gateway between monitoring system and cloud via Ethernet or Wi-Fi.
- Future-proof thanks to over-the-air updates.
- Cost-effective alternative to the Smappee Genius.
- Ensures secured data storage from components.
- 1-day data storage in case of network outage.

The Connect is, similar to the Genius, the gateway between the Power Box and the cloud (Smappee or other), ensuring secure data storage from different components. Data is transferred via Ethernet or Wi-Fi. In the event of a network outage, data will be stored for one day. It only transfers data and does not offer smart control or load balancing functionalities. The Connect is a cost-efficient way to add intelligence to the Smappee Infinity setup.

- **Dimensions:** 55 mm x 55 mm x 26.6 mm (2.17 x 2.17 x 1.05 inches)
- **Weight:** 45 g (1.59 oz)
- **Operating temperature:** -10 °C to 60 °C (14 °F to 140 °F)
- **Storage temperature:** -20 °C to 90 °C (-4 °F to 194 °F)
- **Relative humidity:** 0 % - 95 %, non-condensing
- **Operating altitude:** 0 - 2,000 m (0 - 6,562 feet)
- **EMC:** IEC 61326-1, FCC 47 part 15
- **Safety:** IEC 60950-1
- **Spectrum:** EN 300 328 V2.1.1
- **Product certifications:** CE, FCC, RCM
- **IP rating (IEC 60529):** IP X0
- **Connectivity:**
  - Ethernet 100BASE-T
  - Wi-Fi 2.4 GHz
  - 2 x Smappee Bus B (Modbus RTU)
- **Accessories included:**
  - Wall mounting plate
  - Smappee Bus cable 150 cm (59 inches)