


Smappee Output module



- Add control to the Smappee Infinity ecosystem.
- 2 relay outputs (NO/NC/Common).
- Daisy-chain up to 10 output modules.
- The output modules can easily be added thanks to a quick RJ10 connection.

The Smappee Output module is, next to the Smappee Switch and Smappee scenes, a cost-efficient way to add smart control to the Smappee Infinity ecosystem. The module has 2 separate power relay outputs (dual throw: NO/NC/Common). This allows remote control of devices that are either directly powered (max. 5 A switching capability) or control a breaker (single or 3-phase) to steer high power equipment e.g. a motor, EV charging station, hot water boiler. It can also be used as control signal for smart devices such as Smart Grid Ready heat pumps. You can add up to 10 output modules to the Smappee Infinity setup thanks to its RJ10 connection. The modules communicate via Modbus RTU (RS-485) with the Smappee Genius or any third party data logger.

- **Power supply input range:** 5 - 12 V DC
- **Dimensions:** 55 mm x 55 mm x 26.6 mm (2.17 x 2.17 x 1.05 inches)
- **Weight:** 61 g (2.15 oz)
- **Operating temperature:** -10 °C to 60 °C (14 °F to 140 °F)
- **Storage temperature:** -20 °C to 90 °C (-4 °F to 194 °F)
- **Relative humidity:** 0 % - 95 %, non-condensing
- **Operating altitude:** 0 - 2,000 m (0 - 6,562 feet)
- **Connectivity:** 2 x Smappee Bus B (Modbus RTU)
- **Output connector:**
 - Removable push in spring connection terminal block, 6 positions
 - Solid cable with diameter range 0.5 to 1.5 mm² (20 AWG - 15 AWG). Stranded cable not recommended.
- **Output specifications:**
 - 2 outputs
 - Insulated relays output. 3 contacts per output (NO/NC/C)
 - 5 A max. 250 Vac max.
- **Accessories included:**
 - DIN Mounting plate
 - Smappee Bus cable 150 cm (59 inches)