

Smappee EV Base^{BLACK}



3 phase with two sockets in RAL 7021 (black grey).

- Solar optimisation and autonomous overload protection.
- Real-time and historical charging costs.
- Priority charging, multiple rates and easy payment options with QR code or RFID.
- Works stand-alone or combined with Smappee Infinity for smart features.

The Smappee EV Base is a floor-mounted smart EV charging station with two connectors. When combined with Smappee Infinity, it offers smart charging, ensuring optimised self-consumption and autonomous overload protection. Users and operators receive detailed insights in the charging process and costs via the App and Dashboard. The EV Base is easy to install with simple cable configuration and installation wizard. The integrated LED lighting indicates charging status and ensures sufficient visibility in the parking area. It comes with two sockets and offers multiple payment options via QR codes or RFID.

Dimensions:

1200 × 600 × 150 mm (station)

Weight:

EV Base station: 34 kg

Operating temperature:

-25 °C to 40 °C

Storage temperature:

-25 °C to 60 °C

Relative humidity:

0 % - 95 %, non-condensing

Operating altitude:

0 - 2,000 m

Standards:

IEC 61851-1

Product certifications:

CE

Connectivity:

Ethernet 100BASE-T

Communication protocol:

OCPP 1.6 J, ready for update to OCPP 2.0.1

Mounting method:

Floor

Enclosure:

- Material: Magnelis (structure), aluminium (back plate)
- Rating: IP54 / IK10
- Standard: RAL7021 (black grey)

Integrated Residual Current Protection:

Per connector:
6 mA DC / 30 mA RCD Type A

Required external protection:

Per connector:
Breaker of max. 40 A, type B or C

Charging:

- Maximum charging capacity:
22 kW per connector
- Output power: 230 V/400 V, 32 A
- Charge mode: Mode 3 (IEC 61851)
- Charging activation: QR code / Plug and charge / RFID
- Information status: RGB LED
- MID metering, certified class B

Connectors:

2 x type 2 socket